



\* KEY DIN 6885

FLANGES DIN PN10

DIMENSIONS IN [mm]

SIZE	FLANGE DIMENSIONS						PUMP DIMENSIONS				FOOT DIMENSIONS							SHAFT		WGHT. [kg]		
	IN			OUT			a	f	h1	h2	b	m1	m2	n1	n2	n3	s1	s2	w		d	l
	DN	k	n x Ød	DN	k	n x Ød																
32-25-125	32	100	4x18	25	85	4x14	80	335	112	130	45	66	48	190	150	66	M12	M10	240	24	50	20
32-25-160	32	100	4x18	32	100	4x18	87	385	132	160	63	100	70	240	190	110	M12	M12	285	24	50	26
50-32-125	50	125	4x18	32	100	4x18	80	385	112	140	50	100	70	190	150	110	M12	M12	285	24	50	26
50-32-160	50	125	4x18	32	100	4x18	87	385	132	160	63	100	70	240	190	110	M12	M12	285	24	50	30
50-32-200	50	125	4x18	32	100	4x18	80	385	160	180	63	100	70	240	190	110	M12	M12	285	24	50	40
65-40-200	65	145	4x18	40	110	4x18	100	385	160	180	63	100	70	265	212	110	M12	M12	285	24	50	51
80-50-160	80	160	8x18	50	125	4x18	100	385	160	180	63	100	70	265	212	110	M12	M12	285	24	50	51
100-65-200	100	180	8xM16	65	145	4x18	100	500	180	225	65	125	95	320	250	110	M12	M12	370	32	80	95

NO.	SIZE	CONNECTION
x 1	Ø8	DRAIN
3	M8x1	TEMPERATURE PT100
5	G¼	EXTERN FLUSHING
10	G½	CAN PRESSURE PROTECTION

VALID ONLY WITH SIGNATURE
DATE
SIGNATURE
CUSTOMER
ORDER-NO.
ITEM
CP-NO.